# WISHA Respirator Training Requirements

# Module 3 – Supplied Air Respirators

This module is introductory training for employees who wear supplied air respirators.

Be sure to include worksite-specific information on slides 3, 6, 23, 24 and 25.

Two main types of supplied air respirators are covered in this module. You can delete slides as needed if you only use one kind.

This module only covers basic facts of supplied air respirators and is not complete training by itself.

Employees must also be given hands-on training with the respiratory equipment they will use.

# Using SCBAs – Special Notes

SCBAs are sophisticated respirator equipment used for possible or actual life-threatening situations.

SCBAs should not be used without extensive hands-on training and frequent re-training.

Most SCBA manufacturers or distributors provide this training.

If you have large chemical spill or leak, it may be safer to call professional emergency responders.

SCBA



# **Respirator Training**

# Why Is This Training Required?

Training is required by WISHA for anyone who wears a respirator.

We also are providing this training so you will know how to protect your health.

If you don't know how to use a respirator properly, you can get a false sense of protection.



**Respirator Training** 

# Respirator Program Administrator

Our respirator administrator is [name]

This person is responsible for overseeing our respirator program.

This person has training on respirators.

3

# What are supplied air respirators?

# Two Types







SCBA (self-contained breathing apparatus) – air from a tank

2

# Typical Examples of Use Sandblasting Firefighting Chemical leak or spill response 5 Confined space work

# Where we use supplied air respirators

We use supplied air respirators in the following locations, jobs or situations:

6

# When Are They Required?

Supplied-air respirators are required for protection from:

- ✓ Oxygen deficiency
- √ High levels of toxic chemicals in the air above "IDLH" levels



✓ Other conditions of high levels of highly toxic chemicals in the air

7

# What is Oxygen Deficiency? An oxygen deficiency can be life-threatening Normal air contains 21% oxygen. A space with oxygen content below 19.5% is "oxygen deficient". Lack of oxygen can cause immediate collapse and death. Oxygen deficiency can occur in confined or enclosed spaces or areas of large chemical leaks. 21% Oxygen content

Effects of Oxygen Deficiency				
% Oxygen	<u>Symptoms</u>			
19.5% - 16%	Fatigue, mild impaired coordination			
16% - 12%	Increased breathing rate and pulse; impaired coordination, perception or judgment			
12% - 10%	Further increased breathing rate, blue lips, mental confusion			
10% - 8%	Fainting, nausea, vomiting, mental confusion within few minutes			
8% - 6%	Collapse, death within 8 minutes			
6% - 0%	Coma within 40 seconds, death			

Oxygen deficiency exists

# What is "IDLH"? Immediately Dangerous to Life or Health "IDLH" means immediately dangerous to life or health Many chemicals have a listed IDLH level link to NIOSH IDLH Table Oxygen deficiency is also IDLH IDLH conditions can occur in confined spaces, large chemical spills or leaks and fires

# Entering an IDLH Atmosphere

Several safeguards must be used to enter an area with IDLH conditions:

- ✓ Must have at least one or two standby persons at entrance.
- ✓ Standby employees must be trained to conduct emergency rescue.
- ✓ Appropriate retrieval equipment may be needed.



11

# Escaping an IDLH Atmosphere

In IDLH conditions, a worker may need to escape or immediately leave the area.

An SCBA allows escape at any time.

Airline respirators need a small escape bottle of air attached at the waist.



Airline respirator with emergency escape cylinder

12

# Respirator Air Pressure

# Pressure Demand vs. Demand

Air pressure is controlled by the respirator regulator.

"Pressure-demand" means air flows into the facepiece as needed, but facepiece is always positively-pressured.

"Demand" means air flows into the facepiece only when you inhale.

Only pressure-demand can be used in IDLH conditions.



# Air Flow in Supplied Air Respirators

# Continuous flow airline respirators

"Continuous flow" means air is constantly blowing into the respirator facepiece.

Continuous flow is found in loose-fitting airline respirators.

This type is often more comfortable and hoods can be worn over a beard.

This type cannot be used in IDLH conditions.



Loose-fitting hood



Loose-fitting facepiece

# Supplied Air Respirator Selection

### Conditions Type of Respirator IDLH conditions or SCBA or airline with oxygen deficiency escape bottle Dust/chemical levels Airline with ti up to 1000 times PEL full facepiece Dust/chemical levels Airline with ti up to 50 times PEL half facepiece Airline with Io Dust/chemical levels up to 25 times PEL facepiece

PEL = permissible exposure limit

# Airline Respirator Advantages

# Advantages -

- ✓ continuous air supply,
- √ lightweight,
- √ less maintenance,
- √ don't need to buy tank air

# Limitations-

- ✓ tied to a 300 ft. hose,
- √ depends on output of compressor,
- ✓ need an attached escape bottle in

iaht-fittina			
ight-fitting or full hood			
ight-fitting	· —		
e			
oose			
	ė.		
& Limitations	5		
	5		
- 4			
8 9			
(RI)			
120/			
50			
	<u> </u>		
IDLH conditions			
	<u> </u>		

# SCBA Advantages & Limitations

# **Advantages**

- √ highest form of protection,
- ✓ can be used anywhere,
- ✓ allows unrestricted mobility

## Limitations

- √ heavy & bulky,
- ✓ limited air supply(30 60 min.),
- ✓ extensive training required,
- √ high maintenance




# Air Quality For SCBAs

# Air for breathing must be "Grade D" air

Grade D air for tanks is usually purchased from a specialized supplier.



Grade D air must meet strict requirements. link to WISHA requirements





# Air Quality for Airline Respirators

# Air compressors must deliver clean air

Locate pump intake in an area of clean, fresh air.



Filter air as needed.


Watch out for nearby running engines.

Be sure air intakes are located away from exhaust pipe of an engine compressor.





Small engine compressor



# Construction & Plant Air Compressors

# Use these compressors with caution

Be careful – these do not provide clean air without a filter system!!

Oil-lubricated compressor are especially hazardous. Must test for carbon monoxide or have high temperature alarm.

Engine exhaust can also contaminate breathing air.





21

# Compressor Air Filters

What air filters are needed on compressors?

Moisture trap

Dust filter

Hydrocarbons (oil, solvents) absorbent

Carbon monoxide alarm or hightemp. alarm for oil-lubricated compressors



compressor filters



carbon monoxide alarm

# Compressors We Use Discuss compressors you use here [Optional slide if you use compressors for airline respirators]

# Storage and Maintenance

## **Airline Respirators**

Store facepiece and regulator in clean, dry place. [location]

Coil up hose and store in protected area to prevent damage.

Clean as needed before storage – especially the inside of the facepiece.

Inspect facepiece and hose for damage and replace as needed.



24

# SCBAs Air cylinders must be at least 90% full while in storage. Cylinders must be hydrostatically & Alarm tested every 5 years. Check low pressure alarms and regulators before each use and monthly when not in use. Maintenance is done by [name] Our SCBAs are stored at [location]